

LINIARC® DIRECT/INDIRECT (LDI LED)


PRODUCT HIGHLIGHTS

- **LEDs** - Use of closely-spaced medium power, high-brightness chips minimizes pixelation and provides uniform luminance. Available in 4000K, 3500K and 3000K color temperatures. CRI >=80.
- **Multiple Shielding Options** - Louvers are available in semi-specular aluminum parabolic or white steel flat blades (either solid or perforated).
- **Wide Variety of Distribution Patterns** - Liniarc D/I is available with a wide selection of pattern control covers that allow you to select a distribution pattern that suits your application. From 80% uplight to 100% downlight.
- **Stamped flat end cap standard.**
- **4-Foot Incremental On-Grid Mounting** - Fixtures are available in 4, 8 and 12 foot lengths to match handling capabilities on job site. 4-foot increments allow the fixtures to be mounted on standard ceiling grids, no matter how long the row.
- **Easy Cable Attachment** - No locking plugs are needed with LiniArc fixtures. Hanging connections are secured by the end cap or the adjoining fixture.
- **Less Installation Labor** - Fixtures come with the connecting hardware pre-installed. Keyhole slots capture the joining screws and hold the fixture while the screws are tightened.
- **Easy Two-Way Adjustment** - Finger-action cable grippers on yoke mount allows simple height and side-to-side adjustment, and lock in place with a set screw. This allows the hangers to be pre-set to length on the ground prior to hanging the fixture.




LINIARC LDI WITH PARABOLIC LOUVER AND FLAT END CAPS

DIMENSIONS



DIRECT



INDIRECT

HOUSING - Die Formed 20-gauge steel. Textured white polyester powder coat finish

REFLECTOR - Die formed steel, high-reflectance white polyester powder coat finish.

DRIVER - 0-10V dimming driver standard. SS and HO outputs dim to 1%. VHO output dims to 10%. Universal voltage (120-277 VAC), 347 VAC.

PHOTOMETRICS - Please visit our web site at www.lsi-industries.com for detailed photometric data.

LISTING - U.L. listed to U.S. and Canadian safety standards.

This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.



ACCESSORIES - See Accessories specsheet for Louver, Hanging and Feed options.

LIGHT OUTPUT - LDI LED				
4FT	No Cover	Watts	Solid Cover	Watts
	NW	HO	NW	HO
PL - Parabolic Louver	4244	59	4245	81
FB - Flat Balde Louver	4273	59	4713	81
PB - Perf Flat Blade Louver	4263	59	4769	81

LED Chips are frequently updated therefore values may increase.

ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **LDI 8 LED 50/50 PL HO NW S WHT EM UE**

Prefix	Length	Light Source	Distribution	Shielding	Drive Current	Color Temp	Circuiting	Finish	Emer Circuiting	Options	Voltage
LDI - Direct / Indirect	4 - 4 foot 8 - 8 foot 12 - 12 foot	LED	(Blank) 80% up; 20% down 60/40 60% up; 40% down 50/50 50% up; 50% down 30/70 30% up; 70% down 20/80 20% up; 80% down 100 - 100% down (Distribution patterns are nominal)	PL - Parabolic Louver FB - Flat Blade PB - Perf Flat Blade	SS - Super Saver HO - High Output VHO - Very High Output	30- 3000K 35 - 3500K 40 - 4000K	S-Single	WHT - White BLK - Black SLV - Silver	Blank - None EF - Separate Individual Emergency Feed EH - Dedicated Emergency Thru-Wire Harness ES - Emergency Feed Through Main Single Circuit Harness	RAL - Custom Color (Specify - ex. RAL829) EC - Emergency Circuit Feed F - Fuse GMF - Slow-blow Fuse EM - Emergency Battery Pack LDE1 - Lutron EcoSystem Series H (1% dimming) OCS - Occupancy Sensor DHS - Daylight Harvesting Sensor	UE- Universal Voltage (120-277V) 347 - 347V



Project Name _____ Fixture Type _____
Catalog # _____

09/10/20
© 2020
LSI INDUSTRIES INC.