



Catalog #: \_\_\_\_\_ Project: \_\_\_\_\_

Prepared By: \_\_\_\_\_ Date: \_\_\_\_\_ Type: \_\_\_\_\_

# EMS

## LED Micro Exit Sign



damp location



### FEATURES & SPECIFICATIONS

#### Construction

- Injection-molded UL 94 5VA flame retardant, high temperature thermoplastic housing
- All configurations include field-selectable directional chevrons
- Includes two face plates, a back plate, and mounting canopy bracket
- Standard finish: White

#### Optical System

- Illuminated by long-life, high intensity red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke

#### Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Low voltage disconnect eliminates deep discharge
- Short circuit and Brownout circuit monitor
- Test button to provide manual verification of the transfer circuit and emergency lamps

#### Battery

- Maintenance free NiCad Battery (WB Option Only)

#### Installation

- Includes mounting bracket for ceiling, wall and end mount
- Includes second exit faceplate and back plate

#### Warranty

- 5 year warranty on all electronics and housing
- Separate 5 year pro-rated warranty on the battery

#### Listings

- UL 924 Damp Location
- NFPA 101
- NEC
- CEC
- UL Listed 90 minute emergency run time, 24 hour recharge time

### ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **EMS R WB WH**

Prefix	Letter Color	Battery	Housing Color	Options
EMS - LED Micro Exit Sign	R - Red G - Green	LB - Less Battery (AC Only) WB - With Battery	WH - White	WGB1 - Wire Guard Back Mount WGE - Wire Guard End Mount WGC - Wire Guard Ceiling Mount PGB1 - Poly Guard Back Mount

### PRODUCT DIMENSIONS

