



Catalog # : _____ Project : _____

Prepared By : _____ Date : _____

CWL

Compact Wet Location Emergency Light



FEATURES & SPECIFICATIONS

Construction

- Injection-molded UL 94 V-0 flame retardant, thermoplastic housing
- Standard finish: White and Black

Optical

- Dual adjustable LED lamps with a beam angle of 36°

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Test button to provide manual verification of the transfer circuit and emergency lamps

Battery

- Maintenance free NiCad Battery
- Operating Temperature 0°C to 40°C (32°F to 104°F)

Installation

- Universal J-box mounting pattern with keyhole slots for ceiling and wall mounting

Warranty

- 5 year warranty on all electronics and housing.
- Separate 5 year pro-rated warranty on the battery.

Listings

- UL 924 Wet Location
- cUL
- NFPA 101
- NFPA 70
- NFPA 70
- California Energy Commission (CEC) compliant
- UL Listed 90 minute emergency run time, 24 hour recharge time

Specifications and dimensions subject to change without notice.

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **CWL WH**

Prefix	Housing Color	Options
CWL - Compact Wet Location Emergency Light	WH - White BK - Black	WGB9 - Back Mount Wire Guard

PRODUCT DIMENSIONS

