



Catalog #: _____ Project: _____

Prepared By: _____ Date: _____ Type: _____

ELX

Premium Edge-Lit Exit Sign



damp location



FEATURES & SPECIFICATIONS

Construction

- Specification grade aluminum design with high-clarity acrylic panels
- All configurations include field-selectable directional chevrons
- Standard finish: White, Black, and Satin Aluminum

Optical System

- Illuminated by long-life, high intensity red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke
- NYC Approved - Fully-illuminated 8" characters with 1" stroke in Red only

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz

- Solid-state transfer detects loss of line voltage and automatically switches to emergency mode (SD2 Only)
- Low voltage disconnect eliminates deep discharge
- Brownout circuit monitor
- Test button to provide manual verification of the transfer circuit and emergency lamps

Battery

- Maintenance free sealed Lead Calcium Battery (WB only)
- Maintenance free sealed Ni-MH Battery (SD2 only)
- Operating Temperatures 10°C to 40°C (50°F to 104°F)

Installation

- Mounting Applications: ceiling recessed, wall recessed, surface ceiling, end, or wall mount

Warranty

- 5 year warranty on all electronics and housing
- Separate 5 year pro-rated warranty on the battery

Listings

- UL 924
- NFPA 101
- NEC
- Damp Location Rated
- UL Listed 90 minute emergency run time, 24 hour recharge time

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **ELX U 6 R 1C FC WB WH SD2**

Prefix	Mounting	Character Size	Letter Color
ELX - Premium Edge-Lit Exit Sign	U - Universal Surface Ceiling, End, or Wall Mount RE - Recessed	6 - 6" Tall Letters 3/4" Stroke 8 - 8" Tall Letters 1" Stroke	R - Red G - Green

# of Faces ¹	Chevron	Battery	Housing Color	Options
1C - Single Face Clear 1W - Single Face White 1M - Single Face Mirror 2W - Double Face White 2M - Double Face Mirror	FC - Field Selectable Chevrons	LB - Less Battery WB - With Battery	WH - White BL - Black SA - Satin Aluminum	SD2 ² - Self Test / Self Diagnostic 2CI2 ³ - 2 Circuit Input 120 Volt 2CI27 ³ - 2 Circuit Input 277 Volt PK12 - 12" Pendant Kit PK24 - 24" Pendant Kit PE12 - 12" Pendant Extension PE24 - 24" Pendant Extension

FOOTNOTES:
 1 - Clear panels not available with double face.
 2 - SD2 option comes standard with Ni-MH battery.
 3 - 2CI not available with SD2 units.

PRODUCT DIMENSIONS

