



Catalog #: _____ Project: _____

Prepared By: _____ Date: _____ Type: _____

LPRX

Thermoplastic LED Exit Combo



FEATURES & SPECIFICATIONS

Construction

- Injection-molded UL 94 5VA flame retardant, high temperature, thermoplastic housing
- Universal design includes two faceplates, one backplate, and mounting canopy
- All configurations include field-selectable directional chevrons
- Standard finish: White and Black

Optical System

- Illuminated by long-life, high intensity red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke
- LED Heads - 1.1 Watt per lamp head

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Brownout circuit monitor (SD2 only)
- Low voltage disconnect eliminates deep discharge (SD2 only)
- Test button to provide manual verification of the transfer circuit and emergency lamps
- RL option compatible with up to two SRL remote lamp heads

Battery

- Maintenance free NiCad Battery
- Operating Temperatures 0°C to 40°C (32°F to 104°F)

Installation

- Easy snap together design for effortless installation

- Includes mounting canopy for wall and ceiling mount applications

Warranty

- 5 year warranty on all electronics and housing
- Separate 5 year pro-rated warranty on the battery

Listings

- UL 924
- NFPA 101
- NEC
- CEC
- Damp Location Rated
- UL Listed 90 minute emergency run time, 24 hour recharge time

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **LPRX R U WH LD11 RL**

Prefix	Letter Color	# of Faces	Housing Color	Lamp Heads	Options
LPRX - Thermoplastic Exit Combo	R - Red G - Green	U - Universal (includes two face plates, back plate, and mounting canopy)	WH - White BK - Black	LD11 - 1.1 Watt LED Heads	RL ¹ - 3W Remote Capacity SD2 - Self Test / Self Diagnostic WGB5 - Wire Guard Back Mount

FOOTNOTES:

1 - RL option compatible with up to two SRL remote lamps only

PRODUCT DIMENSIONS

