



Parking Deck Position Guide

*Three designs to satisfy any aesthetic
and performance need:*

- Energy efficient and contractor-friendly lighting solutions
- Linear, square, and round form factors for any environment
- 17 unique optical distributions to provide optimal lighting for any parking deck

EG3



CGC



CPG



XPG4



EXN





OPS





HPG




EG3 PG
6L




CGC
6L - 8L





CPG
6L - 10L










XPG
7L - 10L







EXN
6L - 11L





OPS
6L - 14L



HPG
13L - 23L



Parking Deck Position Guide



	Enclosed & Gasketed (EG3)	Compact (CPG)	Parking Garage (XPG4)	High Output Parking Garage (HPG)	Commercial (CGC)	Opulence (OPS)	Excursion (EXN)
	★★★	★★★	★★★★	★★★★	★★★	★★★★	★★★★★
Markets	Parking Lot / Garage, Petroleum & C-Store	Parking Lot / Garage, Petroleum & C-Store	Automotive, Grocery & Pharmacy, Parking Lot / Garage, Petroleum & C-Store, Retail	Automotive, Commercial, Industrial Manufacturing / Warehousing, Parking Garage	Parking Lot / Garage, Petroleum & C-Store	Automotive, Grocery & Pharmacy, Parking Lot / Garage, Petroleum & C-Store, Retail	Automotive, Grocery & Pharmacy, Parking Lot / Garage, Petroleum & C-Store, Retail
Size L x W x H	Length Varies x 7" x 4"	12" x 12" x 5"	16.5" x 16.5" x 6"	15.86" x 15.86" x 3.68"	18" x 18" x 3.5"	16" x 16" x 4"	17.5" x 17.5" x 5"
Weight	6 - 20 lbs	10 lbs	19 lbs	18.5 lbs	15 lbs	12 lbs	13.5 lbs
Typical Mounting Height	8 - 15'	8 - 15'	8 - 15'	8 - 40'	8 - 15'	8 - 20'	8 - 15'
Mounting	Direct	Pendant or Direct	Pendant or Quick Mount Plate	Pendant or Direct	Pendant or Quick Mount Plate	Pendant or Quick Mount Plate	Pendant or Quick Mount Plate
Surface Conduit Entry	Standard	Standard	Accessory Wiring Box	Accessory Wiring Box	Accessory Wiring Box	Accessory Wiring Box	Accessory Wiring Box
High Voltage	Yes	Yes	Yes	Yes	No	Yes	Yes
Lumen Range	4,000 - 13,000	3,000 - 10,000	3,000 - 10,000	10,000 - 23,000	2,000 - 8,000	3,000 - 14,000	3,000 - 11,000
LPW Range	138 - 144	124 - 144	111 - 132	107-140	119 - 125	125 - 165	122 - 144
IP	67	Wet Location Only	66	66	Wet Location Only	66	Wet Location
DLC ¹	Premium	Premium	Premium	Standard	Standard	Premium	Premium
Lens/Optics	Acrylic	Acrylic	Glass	Acrylic	Acrylic	Acrylic	Acrylic
Distributions	Symmetric	5W	5W	5R	5M	5Q, 5C, 5R, 3W, 4F, 5D, AD	5W, 5N
CCT/CRI	35K8, 40K8, 50K8	30K8, 40K8, 50K8	40K8, 50K8	30K8, 40K8, 50L8	40K7 Only	27K8, 30K8, 35K8, 40K8, 50K8	30K7, 40K7, 50K7
Paint Finishes	White Only	Bronze, White	LSI Standard + Custom Colors	LSI Standard + Custom Colors	Bronze, Gray, White	LSI Standard + Custom Colors	LSI Standard + Custom Colors
Sensors & Controls	Side Mount IMS	Side Mount IMS	Side Mount IMS	AirLink Blue, Airlink Synapse, IMSBT	Microwave	AirLink Blue, IMSBT	AirLink Blue, Airlink Synapse, IMSBT, Lutron Lime Light
Battery Backup	Integral	Deep Housing	Integral	Integral	External Battery Box	Integral	Integral
Uplight	High Angle Light	No	No	Optional 5%	No	Optional 5% or 10%	Optional 3%
Surge Device	Driver Surge Protection Only	Driver Surge Protection Only	Standard 10kV	Optional 10kV	Optional 10kV	Optional 10kV	Optional 10kV
Pricing	\$	\$	\$\$\$	\$\$	\$	\$\$	\$\$

¹ Not all versions of this product may be qualified. Please check the DLC Qualified Products List at www.designlights.org/OPL to confirm which versions are qualified.